

WALL TILES
Care guide and safety

WARNING AND SAFETY
Read fully before installation and use. Retain for future reference.

BEFORE YOU BEGIN




Read all instructions completely before installation and use. Keep packaging and small parts away from children — choking hazard.

TONGUE AND GROOVE



Install using the Tongue & Groove method only; follow the STANLEY Wall Installation Guide. Do not force the profile or glue the joints unless specified.

TRANSPORT & STORAGE



Store boxes flat and level on a clean, dry surface — never on edge. Keep indoors and dry; protect from sunlight, moisture and frost. Transport horizontally.

ACCLIMATISE 48H



Leave unopened boxes in the room of installation for 48 hours before fitting, at 18–25°C. Maintain room climate before, during and after installation.

CUTTING / PPE



Cutting generates dust. Work in a ventilated area and wear eye protection and a dust mask.

STANLEY® WALL TILES - EDITION 9/2026

STANLEY® and the STANLEY logo are registered trademarks of Stanley Black & Decker Inc. and are used under licence. All rights reserved.

Imported and distributed by Area Floors, Kiezel Kleine Brogel 57, 3990 Peer, Belgium.
www.areafloors.com.tr/stanley

WALL TILES
Care guide


USE AND SAFETY IN SERVICE

SPLASHES



Wipe splashes promptly, especially in bathrooms and kitchens. Do not allow water to stand on the joints.

SUNLIGHT




Prolonged direct UV may affect colour over time. Use blinds or curtains in strongly lit areas.

DISPOSAL



Dispose of product and packaging per local regulations. Recycling marks are shown on the box.

DAMP WIPE



Weekly: wipe with a well-wrung cloth or soft sponge and clean water or a pH-neutral cleaner. Work top down and wipe dry. Damp, not wet.

SWEEP / VACUUM



As needed: dust with a soft, dry cloth, or vacuum with a soft brush attachment.

CLASSIFICATION & COMPLIANCE

REACTION TO FIRE	C-s2,d0
WATER RESISTANCE	Waterproof
CE / STANDARD	EN 13245-2:2009
DECLARATION (DOP)	See label
WEAR RESISTANCE	≥ 3.000 cycles

Standards — fire: EN 13501-1 · wear: EN 15468 · CE: EN 13245-2:2009.
DoP No. — see product label. Source: Wall TDS Edition 9/2026

DO

- Wipe splashes promptly
- Keep joints and seams dry
- Ventilate bathrooms and kitchens
- Clean from the top down
- Keep a stable indoor climate

DON'T

- Use steam cleaners
- Use wax, polish or oil
- Use abrasives or solvents
- Let water run into the joints
- Soak the surface

STAIN REMOVAL

ALWAYS TEST ANY CLEANING AGENT ON AN INCONSPICUOUS AREA FIRST.

STAIN TYPE	RECOMMENDED REMOVAL METHOD
DIRT, MUD, FOOD	Damp cloth + pH-neutral cleaner.
GREASE, OIL	Mild detergent solution, then rinse with a damp cloth.
INK, MARKER, LIPSTICK	Isopropyl alcohol on a soft cloth, then wipe clean.
SCUFFS	Soft cloth, light rubbing; pencil eraser for stubborn marks.
CANDLE WAX, CHEWING GUM	Harden with ice, lift gently with a plastic scraper.

LONG-TERM CARE
Check the joints and seams periodically, particularly in bathrooms and kitchens. Keep humid rooms adequately ventilated. Inspect the sealant at wet-area edges and renew it when it fails.

STANLEY® and the STANLEY logo are registered trademarks of Stanley Black & Decker Inc. and are used under licence. All rights reserved.

Imported and distributed by Area Floors, Kiezel Kleine Brogel 57, 3990 Peer, Belgium.
www.areafloors.com.tr/stanley